

TERA-LITE INC. / REVOLAN DIVISION  
1631 SO. 10th ST.  
SAN JOSE, CA. 95211  
Office (408) 288-8655 / Fax (408) 288-9655 / Toll Free (800) 325-0671

## MATERIAL SAFETY DATA SHEET

### SECTION I - PRODUCT IDENTITY

---

Product Identity: Tera-Gem III Decorative Quality (DQ) Epoxy Resin  
Product No: RP 70A  
CAS Chemical Name: Mixture  
Synonyms: None  
Chemical Family: Epoxide  
Product Type: Liquid resin  
Intended use: Epoxy Resin  
Revised date: February 2005  
Revision note: Update MSDS

#### Emergency Overview:

HMIS RATING            Health 2  
                             Flammability 1  
                             Reactivity 0  
                             Protective Equipment X

In case of fire: use carbon dioxide, foam, dry chemicals, water spray with self containing breathing apparatus.

**WARNING:** Skin sensitizer. Can cause allergic skin reaction.

Hazard Statement: IN COMPLIANCE WITH THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200, THIS MATERIAL SAFETY DATA SHEET (MSDS) HAS BEEN PREPARED. THIS MATERIAL IS CONSIDERED TO BE HAZARDOUS UNDER THIS REGULATION.

### SECTION II - INGREDIENTS

---

| <b>%</b> | <b>CAS NO</b> | <b>CHEMICAL NAME</b>  |
|----------|---------------|---|
| >87      | 25068-38-6    | Phenol,4,4-(1-methylethylidene)bis-,polymer with (chloromethyl)oxirane.<br>(Bisphenol A diglycidyl ether polymer)<br>OSHA PEL: None established<br>ACGIH TLV: None established<br>Carcinogen Status: Not reviewed by NTP, IARC OR OSHA. |
| < 4      | 3101-60-8     | 4-(1,1-Dimethylethyl)phenoxyethyl oxirane (p- tertbutyl phenyl glycidyl ether)<br>OSHA PEL: None establishe<br>ACGIH TLV: None established<br>Carcinogen Status: Not reviewed by NTP,   |

IARC or OSHA.

< 4 26447-14-3 4-(methyl)phenoxyethyl oxirane (Cresyl glycidyl ether)  
OSHA PEL: None established  
ACGIH TLV: None established  
Carcinogen Status: Not reviewed NPT,  
IARC OR OSHA.

The remaining components are trade secret

### **SECTION III - HEALTH HAZARDS**

---

Primary Routes of Exposure:

- Ingestion
- Skin Absorption
- Eye Contact
- Inhalation

Exposure Standards:

- No standard has been established for this product. Keep air contaminant concentration in work area to lowest levels

Health Hazard:

- Skin - A single prolonged exposure is unlikely to be absorbed through the skin in harmful amounts. Repeated exposure may cause irritation and/or allergic reaction in humans.
- Eye - A single contact may be moderately irritating to the eyes. Can result in thermal burns if the resin is at elevated temperature.
- Inhalation - Because of its low volatility, this material is not likely to be an inhalation hazard.
- Overexposure effects - Irritation, sensitization and dermatitis Medical conditions aggravated by exposure-Allergy, eczema or skin conditions.

### **SECTION IV - EMERGENCY AND FIRST AID**

---

INGESTION: Give 3-4 glass of water. Do not induce vomiting. If vomiting occurs, give more water. Get medical attention immediate. Have physician determine if emesis induction is necessary.

SKIN CONTACT: Wash with running soap and water for at least 15 minutes. Remove contaminated clothing and shoes and discard or decontaminate before re-use. Seek medical advice immediately.

EYE CONTACT: Flush eyes with eyelids apart with running water for 15 minutes. Get immediate medical help.

INHALATION: If inhaled, remove person to fresh air. Get medical attention if breathing becomes difficult or irritating.

### **SECTION V - SUPPLEMENTAL HEALTH INFORMATION**

---

CARCINOGENICITY:

A recent two-year bioassay of mice receiving skin application of diglycidyl ether of bisphenol A, a similar resin to this product, "have yielded very limited evidence of weak carcinogenicity." The

published study concludes that diglycidyl ether of bisphenol A "is not a systemic carcinogen when applied to the skin of CF 1 mice." and the tumor data " was of no biological importance". Based on all available data, the International Agency for Research on Cancer (IARC) has concluded in 1988 that DGEBA is not classified as a carcinogen.

#### REPRODUCTIVE EFFECTS:

Diglycidyl ether of bisphenol A, a similar resin to this product, has been shown not to interfere with reproduction.

#### MUTAGENICITY:

Diglycidyl ether of bisphenol A, the main part of this product, has tested to be inactive when tested by vivo mutagenicity assay. In vitro mutagenicity studies were negative in some cases and positive in others. The significance of this information to man is unknown.

### **SECTION VI - FIRE AND EXPLOSION HAZARD**

---

|             |  |               |
|-------------|--|---------------|
| Properties: | Flash Point (Tag closed cup)           | 199 C (390 F) |
|             | Upper Explosion Limit (UEL)            | No data       |
|             | Lower Explosion Limit (LEL)            | No data       |
|             | Autoignition Temperature               | No data       |
|             | Fire Hazard Classification (OSHA/NFPA) | Class IIIB    |

Extinguishing Media: Use water fog, foam, dry chemicals or carbon dioxide.

Special Fire Fighting Procedures: Spray and cool fire exposed containers with water. In confined space fire area use NIOSH approved breathing apparatus.

Unusual Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

### **SECTION VII - PERSONAL PROTECTION AND EXPOSURE**

---

Respiratory Protection: In most circumstances not required

Protective Equipment: Use appropriate safety glasses, goggles or face shield for eye protection and protective clothing for skin protection. Wear impervious gloves for hand protection. Use of barrier cream is recommended.

Ventilation: Good general mechanical ventilation with proper exhaust system, providing good air.

### **SECTION VIII - SPILL AND LEAK PROCEDURES**

---

Protect people by keeping unnecessary people away and avoiding all personal contact. For large spill contain material by use of dikes or barrier. Keep out of sewers, storm drains, soil and surface water. Keep fire or spark producing equipments away. For clean-up soak up with absorbent materials such as sand, clay or suitable materials. Residual material may be removed using soapy water. Placed absorbent material in a suitable container to be disposed in accordance with federal, state and local regulations.

## **SECTION IX - PHYSICAL PROPERTIES**

---

Appearance: Slight, pale yellow liquid  
Odor: Faint epoxy odor  
Vapor Pressure: Not applicable  
Vapor Density: Not applicable  
Boiling Point: Not applicable  
Solubility in Water: None  
Specific Gravity: (H<sub>2</sub>O=1) 1.15

## **SECTION X - REACTIVITY AND STABILITY**

---

Chemical Stability: Stable at ambient temperature  
Conditions to Avoid: Elevated temperature over long period  
Incompatible Materials: Acids, bases and oxidizing agents  
Hazardous Decomposition: Carbon monoxide and aldehydes  
Hazardous Polymerization: Will not occur by it self

## **SECTION XI - STORAGE AND HANDLING**

---

Storage: Keep away from acids, oxidizers and heat. Protect containers from physical abuse.  
Handling: Avoid contact to eyes and skin. Avoid excessive breathing of vapor. Smoking and open flame is not permitted in the area.

## **SECTION XII - TOXICOLOGY INFORMATION**

---

Acute Oral Effects (LD<sub>50</sub>) : (Rat) Greater than 5000 mg/kg.  
Acute Dermal Toxicity (LD<sub>50</sub>): (Rabbit) Greater than 6000 mg/kg.  
Inhalation Toxicity (LC<sub>50</sub>): (Rat) Greater than 3466 mg/m<sup>3</sup>  
Sensitization: (Guinea Pig) Skin sensitizes.  
Skin Irritation: (Rabbit) Mild irritation.  
Eye Irritation: (Rabbit) Not an irritant.

## **SECTION XIII - ECOLOGICAL INFORMATION**

No ecological information available.

## **SECTION XIV - TRANSPORTATION INFORMATION**

---

DOT Shipping Name: Resin compound- Not DOT regulated  
IMO Shipping Data: Not DOT regulated  
ICAO/IATA Shipping: Not DOT regulated

## **SECTION XV - REGULATORY INFORMATION**

---

### Federal:

- **SARA TITLE III SEC. 313**  
Under this regulation this product does not contain a toxic chemical for annual Toxic Chemical release reporting under Sec 313 (40 CFR 372).
- **OSHA HAZARD COMMUNICATION STANDARD**  
Under 29 CFR 1910.1200 this product is a "Hazardous Chemical"
- **TSCA INVENTORY STATUS**  
All chemical components of this product are listed on TSCA inventory.
- **CERCLA STATUS**  
Not listed
- **RCRA:**  
Not a hazardous waste under RCRA (40 CFR 372)

### STATE:

- **CALIFORNIA PROPOSITION 65 LISTED CHEMICALS:** None

This information is provided in good faith and is correct to the best of Revolan's knowledge as of the date hereof, and Revolan makes no representation as to its completeness or accuracy. Revolan disclaims responsibility for damages of any kind resulting from the use of this information.

TERA-LITE INC. / REVOLAN DIVISION  
1631 SO. 10th ST.  
SAN JOSE, CA. 95211  
Office (408) 288-8655 / Fax (408) 288-9655 / Toll Free (800) 325-0671

## MATERIAL SAFETY DATA SHEET

### SECTION I - PRODUCT IDENTITY

---

Product Identity: Tera-Gem III DQ (Decorative Quality) Curing Agent  
Product No: RP 70B DQ  
CAS Chemical Name: Mixture  
Synonyms: None  
Chemical Family: Cycloaliphatic amine  
Product Type: Liquid resin  
Intended use: Epoxy curing agent  
Revised date: February 2005  
Revision note: Update MSDS

#### Emergency Overview:

HMIS RATING Health 3  
Flammability 1  
Reactivity 0  
Personal Protection X

In case of fire: use carbon dioxide, foam, dry chemicals, with self-containing breathing apparatus.

**HAZARDS:** Moderate eye, respiratory and skin irritant. May cause skin sensitization.

Hazard Statement: IN COMPLIANCE WITH THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200, THIS MATERIAL SAFETY DATA SHEET (MSDS) HAS BEEN PREPARED.

### SECTION II - HAZARDOUS INGREDIENTS

---

| <u>%</u> | <u>CAS NO</u> | <u>CHEMICAL NAME</u>   |
|----------|---------------|--|
| < 7      | 25620-58-0    | Trimethylhexamethylenediamine (TMD)<br>OSHA PEL: None established<br>ACGIH TLV: None established |
| >20      | 100-51-6      | Benzyl Alcohol<br>OSHA PEL: None established<br>ACGIH TLV: None established                      |
| <23      | 2855-13-2     | Isophoronediamine (IPD)<br>OSHA PEL: None established  |

<15 1761-71-3 ACGIH PEL: None established  
4,4 Methylenebiscyclohexanamine  
OSHA PEL: None established  
ACGIH TLV: None established

The remaining components are trade secret.

### **SECTION III - HEALTH HAZARDS**

---

Primary Routes of Exposure:

- Ingestion
- Skin Absorption
- Eye Contact
- Inhalation

Exposure Standards:

- No standard has been established for this product. Keep air contaminant concentration in work area to lowest levels

Target Organs:

- Eyes, skin and respiratory systems.

Health Hazards:

- Corrosive liquid which may cause severe eye, skin and respiratory tract irritation. May cause skin sensitization.

Sign and Symptoms of Exposure (Acute Effects):

- Material vapor in low concentration can cause lacrimation, conjunctivitis and corneal edema when absorbed into the tissue of the eye from the atmosphere. This may give rise to a perception of "blue haze" or "fog" around lights. The effect is transitory and has no know lasting effect. Inhalation of the vapor, mist or fog may cause irritation in the respiratory tract and other harms. Eyes and skin contact with the undiluted material will quickly cause severe irritation and pain and may lead to burns, necrosis and permanent injury. Ingestion may cause bleeding of the gastrointestinal tract and vomiting of blood.

Sign and Symptoms of Exposure (Possible Longer Term Effects)

- Repeated and prolonged exposure may cause allergic reaction/sensitization, adverse respiratory effects ( cough, tightness of chest or shortness of breath), adverse eye effects (conjunctivitis or corneal damage) and/or adverse skin effects (defatting, rash, irritation). Prolonged or repeated vapor inhalation effects may be delayed and which may cause dryness of nasal passages and sore throat. Medical Conditions Generally Aggravated By Exposure Asthma, chronic respiratory disease, eye disease, skin disorders and allergies.

### **SECTION IV - EMERGENCY AND FIRST AIDS**

---

INGESTION: Give 3-4 glass of water or milk. Do not induce vomiting. If vomiting occurs, give more water. Get medical advice.

- SKIN CONTACT:** Wash with running soap and water for at least 15 minutes. Remove contaminated clothing and shoes and discard or decontaminate before re-use. Seek medical advice.
- EYE CONTACT:** Flush eyes with eyelids apart with running water for 15 minutes. Get medical help.
- INHALATION:** If breathing is stopped or is labored, remove person to fresh air and give assisted respiration. Prevent person from vomiting. Get medical attention if breathing becomes difficult or irritating.

## **SECTION V - FIRE AND EXPLOSION HAZARD**

---

|             |  |                |
|-------------|--|----------------|
| Properties: | Flash Point (Closed Cup)               | >93 C (>200 F) |
|             | Upper Explosion Limit (UEL)            | No data        |
|             | Lower Explosion Limit (LEL)            | No data        |
|             | Autoignition Temperature               | No data        |
|             | Fire Hazard Classification (OSHA/NFPA) | Class IIIB     |

**Extinguishing Media:** Use water fog, foam, dry chemicals or carbon dioxide.

**Special Fire Fighting Procedures:** Spray and cool fire exposed containers with water. Fire fighters should be protected with butyl rubber gloves, boots and body suit. In confined space fire area use self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards:** Decomposition and combustion products may be toxic. Sudden reaction and fire may result if the product is mixed with an oxidizing agent. Evacuate personnel in vicinity and downwind.

## **SECTION VI - PERSONAL PROTECTION AND EXPOSURE**

---

**Respiratory Protection:** In poorly ventilated area A NIOSH approved organic vapor respirator is recommended.

**Protective Equipment:** Use approved splash proof safety glasses, goggles or face shield for eye protection. Wear protective clothing resistant to this product. Immediately remove contaminated clothing and wash exposed skin with soap and water

**Ventilation:** Good general mechanical ventilation with proper exhaust system, providing good air flow.

## **SECTION VII - SPILL AND LEAK PROCEDURES**

---

Protect people by keeping unnecessary people away and avoiding all personal contact. For large spill contain material by using dike or barrier. Keep out of sewers, storm drains, soil and surface water. Keep fire or spark producing equipment away. For clean-up soak up with absorbent materials such as sand, clay or suitable materials. Residual material may be removed using soapy water. Placed absorbent material in a suitable container to be disposed in accordance with federal, state and local regulation



## **SECTION VIII - PHYSICAL PROPERTIES**

---

Appearance: Colorless liquid  
Odor: Ammoniacal odor  
Vapor Pressure: mm Hg/21 C <10.34  
Vapor Density: No data  
Boiling Point: 205 C (401 F)  
Solubility in Water: Slight  
Specific Gravity: (H2O=1) 1.047  
Evaporation Rate: No data

## **SECTION IX - REACTIVITY AND STABILITY**

---

Chemical Stability: Stable at ambient temperature  
Conditions to Avoid: Not applicable  
Incompatible Materials: Acids and oxidizing agents  
Hazardous Decomposition: Carbon monoxide and nitrogen oxides in fire. Ammonia and hydrogen cyanide when heated. Under oxygen-starved conditions combustion products like nitrile, cyanic acid, isocyanates, cyanogens and carbamate are formed.

## **SECTION X - STORAGE AND HANDLING**

---

Storage: Keep away from acids, oxidizers and heat. Protect containers from physical abuse.  
Handling: Avoid contact to eyes and skin. Avoid excessive breathing of vapor. Smoking and open flame is not permitted in the area.

## **SECTION XI - TOXICOLOGICAL PROPERTIES**

---

Acute Oral Toxicity: (LD 50, Rat) >1750 mg/kg (Estimate)  
Acute Dermal Toxicity: (LD 50, Rabbit) >1840 mg/kg (Estimate)  
Acute Inhalation Toxicity: (LD 50, Rat) No Data  
Other Acute Effects: No Data  
Irritation Effects Data: Corrosive to the skin of rabbit  
Chronic/Subchronic Data: No delayed chronic or subchronic test data are known.

## **SECTION XII - ECOLOGICAL INFORMATION**

---

Ecotoxicity: No Data  
Environmental Fate: No Data

## **SECTION XIII - DISPOSAL CONSIDERATIONS**

---

Comply with all federal, state and local regulations. May incinerate in admixture with fuel equipped with scrubber to remove nitrogen oxide and carbon monoxide.

## **SECTION XIV - TRANSPORTATION INFORMATION**

---

DOT Non-Bulk Shipping Name: Amine. Liquid. Corrosive. n.o.s.  
Trimethylhexamethylenediamine);  
8; UN2735; PG II

IMO Shipping Data: Amine. Liquid. Corrosive. n.o.s.  
Trimethylhexamethylenediamine);  
8; UN2735; II;  
HazMat STCC=4935601; EMS No 8-05;  
MFAG No 320

ICAO/IATA Shipping Data: Amine. Liquid. Corrosive. n.o.s.  
Trimethylhexamethylenediamine);  
8; UN2735; II;  
Shipment per 49CFR 171.11

## **SECTION XV - REGULATORY INFORMATION**

---

### Federal:

- SARA TITLE III SEC. 312 and SEC.313  
Under this regulation this product is classified as an "immediate health hazard" and under sec. 313 there are no components above the "de minimis level."
- OSHA HAZARD COMMUNICATION STANDARD  
Under 29 CFR 1910.1200 this product is a "Corrosive"
- TSCA INVENTORY STATUS  
All chemical components of this product are listed on TSCA inventory.
- CERCLA STATUS  
Not listed

### STATE:

- CALIFORNIA PROPOSITION 65 LISTED CHEMICAL: None

This information is provided in good faith and is correct to the best of Revolan's knowledge as of the date hereof, and Revolan makes no representation as to its completeness or accuracy. Revolan disclaims responsibility for damages of any kind resulting from the use of this information.